

PROFESSIONAL VIDEO SECURITY SOLUTION



www.sperado.com

PROFESSIONAL CAMERA

SHC-4220



2MP 4 IN 1 BULLET CAMERA

- 1/3" Scan Galaxy Core CMOS
- Max. 2.0MP (1920x1080), Full HD
- Min. Illumination:0.01Lux,0Lux (IR) Smart IR, Max IR Distance 25Meter
- 3MP 2.8mm or 3.6mm Fixed Lens
- DWDR, 3D-DNR Support
- Weather Proof IP-66 Standard
- Support UTC (Up the Coax)



2MP 4 IN 1 DOME CAMERA

• 1/3" Scan Silicon Optronics CMOS

• Max, 2.0MP (1920x1080), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

• Smart IR, Max IR Distance 30Meter

• 3MP 2.8mm or 3.6mm Fixed Lens

• DWDR, 3D-DNR Support

• Support UTC (Up the Coax)

• Weather Proof IP-66 Standard



• Smart IR, Max IR Distance 30Meter

SHC-4221

- 3MP 2.8mm or 3.6mm Fixed Lens • DWDR, 3D-DNR Support
- Weather Proof IP-66 Standard

SHC-6221

2MP 4 IN 1 DOME CAMERA

• 1/3" Scan Silicon Optronics CMOS

• Max, 2.0MP (1920x1080), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

• Smart IR, Max IR Distance 30Meter

• 3MP 2.8mm or 3.6mm Fixed Lens

SHC-4226

• DWDR, 3D-DNR Support

• Weather Proof IP-66 Standard

• Support UTC (Up the Coax)

• Support UTC (Up the Coax)



2MP 4 IN 1 BULLET CAMERA • 1/3" Scan Galaxy Core CMOS

- Max. 2.0MP (1920x1080), Full HD
- Min. Illumination:0.01Lux,0Lux (IR)
- Smart IR, Max IR Distance 30Meter
- 3MP 2.8mm or 3.6mm Fixed Lens • DWDR, 3D-DNR Support
- Weather Proof IP-66 Standard
 - Support UTC (Up the Coax)

SHC-6222

2MP 4 IN 1 DOME CAMERA

• 1/3" Scan Silicon Optronics CMOS

• Max. 2.0MP (1920x1080), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

• Smart IR, Max IR Distance 30Meter

• 3MP 2.8mm or 3.6mm Fixed Lens

SHC-4227

• Weather Proof IP-66 Standard

• Support UTC (Up the Coax)

• DWDR, 3D-DNR Support



2MP 4 IN 1 BULLET CAMERA

• Max. 2.0MP (1920x1080), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

Smart IR,Max IR Distance 30Meter

• 3MP 2.8mm or 3.6mm Fixed Lens

SHC-2220

2MP 4 IN 1 DOME CAMERA

• 1/3" Scan Silicon Optronics CMOS

• Max. 2.0MP (1920x1080), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

• Smart IR, Max IR Distance 30Meter

• 3MP 2.8mm or 3.6mm Fixed Lens

• DWDR, 3D-DNR Support

• Weather Proof IP-54 Standard

• Support UTC (Up the Coax)

• DWDR, 3D-DNR Support

• Weather Proof IP-66 Standard

• Support UTC (Up the Coax)

• 1/3" Scan Galaxy Core CMOS

SHC-4224

2MP 4 IN 1 BULLET CAMERA

- 1/3" Scan Sony CMOS
- Max. 2.0MP (1920x1080), Full HD • Min. Illumination:0.01Lux,0Lux (IR)
- Smart IR, Max IR Distance 30Meter
- 3MP 2.8mm or 3.6mm Fixed Lens • DWDR, 3D-DNR Support
- Weather Proof IP-66 Standard
- Support UTC (Up the Coax)

SHC-2221



2MP 4 IN 1 DOME CAMERA

1/3" Scan Sonv CMOS

- Max. 2.0MP (1920x1080), Full HD
- Min. Illumination:0.01Lux,0Lux (IR) Smart IR, Max IR Distance 30Meter
- 3MP 2.8mm or 3.6mm Fixed Lens

SHC-4229

2MP 4 IN 1 BULLET CAMERA

• Max. 2.0MP (1920x1080), Full HD

• Min. Illumination:0.01Lux.0Lux (IR)

Smart IR.Max IR Distance 40Meter

• 3MP 2 8mm or 3 6mm Fixed Lens

• Weather Proof IP-66 Standard

• Support UTC (Up the Coax)

• 1/3" Scan Sony CMOS

• DWDR, 3D-DNR Support

- DWDR, 3D-DNR Support
- Weather Proof IP-54 Standard
- Support UTC (Up the Coax)

SHC-4225



2MP 4 IN 1 BULLET CAMERA

- 1/3" Scan Sony CMOS
- Max, 2.0MP (1920x1080), Full HD
- Min. Illumination:0.01Lux.0Lux (IR)
- Smart IR.Max IR Distance 40Meter
- 3MP 2 8mm or 3 6mm Fixed Lens

SHC-4423

4MP 4 IN 1 BULLET CAMERA

• Max. 4.0MP (2688x1520), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

• Smart IR, Max IR Distance 30Meter

SAS-8516

16 CHANNEL HYBRID (5 IN 1) DVR

• Connect to HDTVI,CVI,AHD,Analog

• Support All Channel IP Cameras

• Up to 5MP Resolution Recording

Support P2P (P6pro Application)

• H.265+/H.264+ compression

• Support UTC (Up the Coax)

• Face Detection Technology

• Support 2 HDD up to 6 TB

• 5MP 2.8mm or 3.6mm Fixed Lens

• DWDR, 3D-DNR Support

Weather Proof IP-66 Standard

• Support UTC (Up the Coax)

• 1/3" Scan OmniVision CMOS

- DWDR, 3D-DNR Support
- Weather Proof IP-66 Standard
- Support UTC (Up the Coax)

2MP 4 IN 1 BULLET CAMERA

- 1/3" Scan Sony CMOS • Max, 2.0MP (1920x1080), Full HD
- Min. Illumination:0.01Lux.0Lux (IR)
- Smart IR.Max IR Distance 40Meter
- 3MP 2 8mm or 3 6mm Fixed Lens
- DWDR, 3D-DNR Support

SHC-4428

4MP 4 IN 1 BULLET CAMERA

• Max. 4.0MP (2688x1520), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

• Smart IR, Max IR Distance 50Meter

• 5MP 2.8mm or 3.6mm Fixed Lens

SAS-8516D

16 CHANNEL HYBRID (5 IN 1) DVR

• Connect to HDTVI,CVI,AHD,Analog

• Support All Channel IP Cameras

• Up to 5MP Resolution Recording

Support P2P (P6pro Application)

• H.265+/H.264+ compression

• Support UTC (Up the Coax)

• Face Detection Technology

Support 1 HDD up to 6 TB

• DWDR, 3D-DNR Support

Weather Proof IP-66 Standard

• Support UTC (Up the Coax)

• 1/3" Scan OmniVision CMOS

- Weather Proof IP-66 Standard
- Support UTC (Up the Coax)



1/3" Scan Sony CMOS

- Max, 2.0MP (1920x1080), Full HD
- Min. Illumination:0.01Lux.0Lux (IR)
- Smart IR.Max IR Distance 40Meter
- 3MP 2 8mm or 3 6mm Fixed Lens
- DWDR, 3D-DNR Support
- Weather Proof IP-66 Standard
- Support UTC (Up the Coax)

SHC-6420

4MP 4 IN 1 DOME CAMERA

• Max. 4.0MP (2688x1520), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

• Smart IR, Max IR Distance 30Meter

SAS-8508/8504

8/4 CHANNEL HYBRID (5 IN 1) DVR

• Connect to HDTVI,CVI,AHD,Analog

• Support All Channel IP Cameras

• Up to 5MP Resolution Recording

Support P2P (P6pro Application)

• H.265+/H.264+ compression

• Support UTC (Up the Coax)

• Face Detection Technology

• Support 1 HDD up to 6 TB

• 5MP 2.8mm or 3.6mm Fixed Lens

• DWDR, 3D-DNR Support

Weather Proof IP-66 Standard

• Support UTC (Up the Coax)

• 1/3" Scan OmniVision CMOS



SHC-4228

2MP 4 IN 1 BULLET CAMERA

- 1/3" Scan Sony CMOS • Max, 2.0MP (1920x1080), Full HD
- Min. Illumination:0.01Lux.0Lux (IR)
- Smart IR.Max IR Distance 50Meter
- 3MP 2 8mm or 3 6mm Fixed Lens • DWDR, 3D-DNR Support
- Weather Proof IP-66 Standard
- Support UTC (Up the Coax)

SHC-4230

2MP 4 IN 1 BULLET CAMERA

• Max. 2.0MP (1920x1080), Full HD

• Min. Illumination:0.01Lux,0Lux (IR)

• Smart IR, Max IR Distance 40Meter

SAS-8216

16 CHANNEL HYBRID (5 IN 1) DVR

• Connect to HDTVI,CVI,AHD,Analog

• Support All Channel IP Cameras

• Up to 2MP Resolution Recording

Support P2P (Xmeye Application)

• H.265+/H.264+ compression

• Support UTC (Up the Coax)

Support Motion Detection

• Support 2 HDD up to 6 TB

• 3MP 2.8~12mm Vari Focal Lens

Weather Proof IP-66 Standard

• Support UTC (Up the Coax)

• DWDR, 3D-DNR Support

• 1/3" Scan Sony CMOS

SHC-6230



2MP 4 IN 1 DOME CAMERA

- 1/3" Scan Sony CMOS
- Max. 2.0MP (1920x1080), Full HD
- Min. Illumination:0.01Lux,0Lux (IR) • Smart IR, Max IR Distance 40Meter
- 3MP 2.8~12mm Vari Focal Lens
- DWDR, 3D-DNR Support
- Weather Proof IP-66 Standard
- Support UTC (Up the Coax)

SAS-8208/8204



8/4 CHANNEL HYBRID (5 IN 1) DVR

- H.265+/H.264+ compression
- Connect to HDTVI,CVI,AHD,Analog
- Support All Channel IP Cameras

Support P2P (Xmeye Application)

• Up to 2MP Resolution Recording • Support UTC (Up the Coax) Support Motion Detection

• Support 1 HDD up to 6 TB